

COMMUNITY CONSERVATION ASSISTANCE PROGRAM
DETAILED IMPLEMENTATION PLAN
PY2015



All practices defined below are to be maintained by the landowner of a single-family residence for a five-year period; all other types of properties are to be maintained by the landowner for a 10-year period.

Definition of Practices

- (1) Abandoned well closure is the sealing and permanent closure of a supply well no longer in use. This practice serves to prevent entry of contaminated surface water, animals, debris or other foreign substances into the well. It also serves to eliminate the physical hazards of an open hole to people, animals and machinery.
- (2) Bioretention area is the use of plants and soils for removal of pollutants from stormwater runoff. Bioretention can also be effective in reducing peak runoff rates, runoff volumes and recharging groundwater by infiltrating runoff. Bioretention areas are intended to treat impervious surface areas of greater than 2500 ft².
- (3) A backyard rain garden is a shallow depression in the ground that captures runoff from a driveway, roof, or lawn and allows it to soak into the ground, rather than running across roads, capturing pollutants and delivering them to a stream. Backyard rain gardens are intended to treat impervious surface areas of less than 2500 ft².
- (4) Stormwater wetland means a constructed system that mimics the functions of natural wetlands and is designed to mitigate the impacts of stormwater quality and quantity. Stormwater wetlands are intended to treat impervious surface areas of greater than 2500 ft².
- (5) Backyard wetlands are constructed systems that mimic the functions of natural wetlands. They can temporarily store, filter and clean runoff from driveways, roofs and lawns, and thereby improve water quality. The wetland should be expected to retain water or remain saturated for two to three weeks. Backyard wetlands are intended to treat impervious surface areas of less than 2500 ft².
- (6) A cistern is a system of collection and diversion practices to prevent stormwater from flowing across impervious areas, collecting sediment and reaching the storm drains. Benefits may include the reduction of stormwater runoff thereby reducing the opportunity for pollution to enter the storm drainage system.
- (7) A critical area planting means an area of highly erodible land, which cannot be stabilized by ordinary conservation treatment on which permanent perennial vegetative cover is established and protected to improve water quality. Benefits may include reduced soil erosion and sedimentation and improved surface water quality.
- (8) A diversion means a channel constructed across a slope with a supporting ridge on the lower side to control drainage by diverting excess water from an area to improve water quality.

- (9) A grassed swale consists of a natural or constructed channel that is shaped or graded to required dimensions and established in suitable vegetation for the stable conveyance of runoff to improve water quality. Benefits may include reduced soil erosion, and sedimentation and improve the quality of surface water pollution from dissolved and sediment-attached substances.
- (10) Impervious surface conversion means the removal of impenetrable materials such as asphalt, concrete, brick and stone. These materials seal surfaces, repel water and prevent precipitation from infiltrating soils. Removal of these impervious materials, when combined with permeable pavement or vegetation establishment, is intended to reduce stormwater runoff rate and volume, as well as associated pollutants transported from the site by stormwater runoff.
- (11) Permeable pavement means materials that are designed to allow water to flow through them and thus reduce the imperviousness of traffic surfaces, such as patios, walkways, sidewalks, driveways and parking areas.
- (12) A pet waste receptacle means a receptacle designed to encourage pet owners to pick up after animals in parks, neighborhoods and apartment complexes so as to prevent waste from being transported off-site by stormwater runoff.
- (13) A riparian buffer means an area adjacent to a stream where a permanent, long-lived vegetative cover (sod, shrubs, trees or a combination of vegetation types) is established to improve water quality. Benefits may include reduced soil erosion, sedimentation, pathogen contamination and pollution from dissolved, particulate and sediment-attached substances.
- (14) A stream restoration system means the use of bioengineering practices, native material revetments, channel stability structures and/or the restoration or management of riparian corridors to protect upland BMPs, restore the natural function of the stream corridor and improve water quality by reducing sedimentation to streams from streambanks.
- (15) Streambank and shoreline protection means the use of vegetation to stabilize and protect banks of streams, lakes, estuaries or excavated channels against scour and erosion.
- (16) Marsh sills protect estuarine shorelines from erosion, combining engineered structures with natural vegetation to maintain, restore, or enhance the shoreline's natural habitats. A sill is a coast-parallel, long or short structure built with the objective of reducing the wave action on the shoreline by forcing wave breaking over the sill. Sills are used to provide protection for existing coastal marshes, or to retain sandy fill between the sill and the eroding shoreline, to establish suitable elevations for the restoration or establishment of coastal marsh and/or riparian vegetation.
- (17) A structural stormwater conveyance includes various techniques to divert runoff from paved surfaces where a vegetated diversion is not feasible. The purpose is to direct stormwater runoff (sheet flow or concentrated) away from a direct discharge point and divert it to an approved BMP or naturally vegetated area capable of removing nutrients through detention, filtration, or infiltration.